


PB DP FC 1x2xAWG22/1 LSHF-FR + PE

PROFIBUS FC LSHF-FR Cable with additional PE-Sheath, 150 Ohm



Application

Installation cable (up to inner sheath) :

- Halogen free and flame resistant
- Limited segment length (according to PROFIBUS-Net Manual)
- FastConnect-assembly
- UV-resistant
- Silicon free
- Limited oil and grease resistance

Standards

- Customer specification

Fire Rating

Basic cable:

- IEC 60332-1, IEC 60332-3-24, IEC 61034-2, IEC 60754-1/2

Construction

Conductor	bare copper wire, \emptyset 0.64 mm, (cross-section 0.32 mm ²)
Insulation	foam-skin-PE, \emptyset 2.5 mm
Stranding	two cores gn / rd to the Pair
Bedding	halogen free, flame retardant thermoplastic sheathing compound acc. to EN 50290-2-27, filling the interstices \emptyset 5.4 mm
Static screen	PET-Al-Foil longitudinally applied
Braid	tinned copper braid, coverage approx. 60%
Inner Sheath	halogen free, flame retardant thermoplastic sheathing compound acc. to EN 50290-2-27, violet, \emptyset 8.0 mm
Outer Sheath	PE, blue or black, \emptyset 10.8 mm
Outer Diameter	Nom. 10.8 mm
Weight	Nom. 122 kg/km

Mechanical Properties

Bending radius	
single bending	$\geq 10 \times D$
repeated bending	$\geq 15 \times D$
Temperature range	- 25°C to + 70°C
Transport and storage	- 25°C to + 70°C
Installation	- 25°C to + 50°C

Electrical Properties at 20°C

Loop resistance	$\leq 110 \Omega/\text{km}$
Screen resistance	$\leq 9.5 \Omega/\text{km}$
Characteristic impedance (Nominal)	150 Ω
Mutual capacitance (at 1 kHz)	ca. 28.5 nF/km
Insulation resistance	$\geq 5 \text{ G}\Omega/\text{km}$
Test Voltage (DC, 1 min) Core/Core and Core/Screen	1 kV
Operating voltage (RMS)	$\leq 100 \text{ V}$

Electrical Data at 20°C

Frequency (kHz)	Impedance (Ohm)	Attenuation (dB/100m)
9.6 kHz	270 \pm 27	≤ 0.25
38.4 kHz	185 \pm 18.5	≤ 0.4
1 MHz	-	-
3 MHz	150 \pm 15	-
4 MHz	150 \pm 15	≤ 2.2
16 MHz	150 \pm 15	≤ 4.2
20 MHz	150 \pm 15	-

Ordering Information

P/N	Product Description	P.U
1027325	1 x 2 x 0.64/2.55-150, PROFIBUS FC LSHF-FR Cable with additional PE-Sheath, PB DP FC 1x2xAWG22/1 LSHF-FR + PE	1000m/drum
1027326	1 x 2 x 0.64/2.55-150, PROFIBUS FC LSHF-FR Cable with additional PE-Sheath, PB DP FC 1x2xAWG22/1 LSHF-FR + PE	1000m/drum