



## TWINAXIAL SPEAKER CABLES LSZH REFLEX LSZH

**TS 215 LSZH**

✓STUDIO ✓INSTALLATION ✓STAGE

ISO9001 CERTIFIED ROHS COMPLIANT REACH CE

HFFR OFC ANALOG

**TS 415 LSZH**

### APPLICATION

These Reflex professional speaker cables are originally designed to deliver maximum performance from state-of-the-art Tri-Amp Systems. Extra-tough jacket and oversized heavy-duty construction for exceptional ruggedness and durability. Ivox speaker cable products have low smoke density, halogen free and they don't emit poisonous gases.

### CONSTRUCTION DATA

Core Section:	1,50 mm <sup>2</sup> (16 AWG)
Stranded Copper Conductor	84 x 0,15 mm ø Stranded Bare Copper (16 AWG)
Conductor Insulation	2,80 ± 0,05 mm ø Hffr Compound
Conductor Color Code	Blue / Red / Yellow / Green
Outer Sheath	Hffr Compound Black

	<b>TS 215</b>	<b>TS 415</b>
Core Numbers x Section:	2 x 1,50 mm <sup>2</sup>	4 x 1,50 mm <sup>2</sup>
Outer Diameter	7 ± 0,10 mm ø	8,50 ± 0,10 mm ø
Weight	7,6 kg/100 m	12,8 kg/100 m

### ELECTRICAL DATA

Conductor Resistance	< 12,5 Ω / km
Insulation Resistance	> 2000 MΩ x km
Capacitance core/core	150 pF / m
Inductance	0.56 μH / m
Test voltage	2 kV
Max. Operating Voltage	300 V

### MECHANICAL DATA

Minimum bending radius	8 x D ( D= outer diameter )
Temperature range Fixed installation	-30° C to + 70° C

■ BLACK