



## TWINAXIAL SPEAKER CABLES REFLEX



**TS 215**

✓ MOBILE ✓ STUDIO ✓ INSTALLATION ✓ STAGE

sPVC

OFC

ANALOG

**TS 415**

### APPLICATION

These Reflex professional speaker cables are originally designed to deliver maximum performance from state-of-the-art Tri-Amp Systems. Extra-tough jacket and oversized heavy-duty construction for exceptional ruggedness and durability.

### CONSTRUCTION DATA

Core Section	1,50 mm <sup>2</sup> (16 AWG)
Stranded Copper Conductor	84 x 0,15 mm ø Stranded Bare Copper (16 AWG)
Conductor Insulation	2,80 ± 0,05 mm ø PVC
Conductor Color Code	Blue / Red / Yellow / Green
Outer Sheath	sPVC Matt Black

Core Numbers x Section  
Outer Diameter  
Weight

#### TS 215

2 x 1,50 mm<sup>2</sup>  
7 ± 0,10 mm ø  
7,6 kg/100 m

#### TS 415

4 x 1,50 mm<sup>2</sup>  
8,50 ± 0,10 mm ø  
12,8 kg/100 m

### ELECTRICAL DATA

Conductor Resistance	< 12,5 Ω / km
Insulation Resistance	> 2000 MΩ x km
Capacitance	
	core/core
	150 pF / m
Inductance	0.56 μH / m
Test voltage	2 kV
Max. Operating Voltage	300 V

### MECHANICAL DATA

Minimum bending radius	5 x D ( D= outer diameter )
Temperature range	
Mobile installation	- 5° C to + 70° C
Fixed installation	-30° C to + 70° C

■ BLACK

